

Appl. No. 09/80,602
Amdt. Dated July 27, 2006
Reply to Final Office action of May 3, 2006

RECEIVED
CENTRAL FAX CENTER
JUL 27 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (canceled) An apparatus comprising:
a first memory having KN locations to store K sums of mixer samples during an epoch interval, the mixer samples being generated at a first clock frequency from a mixer for N channels corresponding to N satellites in a global positioning system (GPS) receiver;
an address counter coupled to the first memory to generate an address modulo-KN corresponding to a first location in the first memory at the first clock frequency; and
an adder coupled to the mixer and the first memory to add one of the mixer samples to contents of the first location to generate a sum, the sum being written into the first location.
2. (canceled) The apparatus of claim 1 further comprising:
a second memory coupled to the first memory and the address counter to store the K sums of mixer samples transferred from the first memory at end of the epoch interval.
3. (canceled) The apparatus of claim 1 further comprising:
an epoch control circuit to generate an epoch signal indicative of the epoch interval.
4. (canceled) The apparatus of claim 3 wherein the epoch control circuit comprises:
N epoch interval generators to generate N channel interval signals;
a decoder to enable one of the N epoch interval generators; and
a multiplexer coupled to the N epoch interval generators to select one of the N channel interval signals, the selected one of the N channel interval signals corresponding to the epoch signal.
5. (canceled) The apparatus of claim 1 wherein $K = 22$ and $N = 12$.
6. (canceled) The apparatus of claim 5 wherein the first clock frequency is equal to twenty-four times a coarse/acquisition chip rate of the GPS receiver.

Appl. No. 09/80,602

Amdt. Dated July 27, 2006

Reply to Final Office action of May 3, 2006

7. (canceled) An apparatus comprising:
- a mixer circuit to mix a de-spreaded sample with coefficients to generate a mixer sample at a first clock frequency, the de-spread sample being provided by a dc-spreader circuit for a signal received from one of N satellites in a global positioning system (GPS);
 - a look-up table coupled to the mixer circuit to generate the coefficients based on a carrier numerically controlled oscillator (NCO) value; and
 - a carrier NCO coupled to the look-up table to generate a carrier NCO value.
8. (canceled) The apparatus of claim 7 wherein the dc-spread sample includes de-spread in-phase and de-spread quadrature components, each component having 6 bits.
9. (canceled) The apparatus of claim 8 wherein the coefficients include a sine and cosine values, each value having three bits.
10. (canceled) The apparatus of claim 9 wherein the mixer sample includes mixer in-phase and quadrature components.
11. (previously presented) An apparatus comprising:
- a mixer circuit to mix a de-spreaded sample with coefficients to generate a mixer sample at a first clock frequency, the de-spread sample being provided by a de-spreader circuit for a signal received from one of N satellites in a global positioning system (GPS), the de-spread sample includes de-spread in-phase and de-spread quadrature components, each component having 6 bits, the mixer sample including mixer in-phase and quadrature components, the mixer circuit comprising:
 - an in-phase circuit to generate the mixer in-phase component based on a first complex multiplication on the de-spread in-phase and quadrature components and the sine and cosine values, the mixer in-phase component having 8 bits $[[;]]$, and
 - a quadrature circuit to generate the mixer quadrature component based on a second complex multiplication on the de-spread in-phase and quadrature components and the sine and cosine values, the mixer quadrature component having 8 bits;

Appl. No. 09/80,602
Amdt. Dated July 27, 2006
Reply to Final Office action of May 3, 2006

a look-up table coupled to the mixer circuit to generate the coefficients based on a carrier numerically controlled oscillator (NCO) value, the coefficients including sine and cosine values, each value having three bits; and

a carrier NCO coupled to the look-up table to generate a carrier NCO value.

12. (previously presented) An apparatus comprising:

a mixer circuit to mix a de-spreaded sample with coefficients to generate a mixer sample at a first clock frequency, the de-spread sample being provided by a de-spreader circuit for a signal received from one of N satellites in a global positioning system (GPS);

a look-up table coupled to the mixer circuit to generate the coefficients based on a carrier numerically controlled oscillator (NCO) value; and

a carrier NCO coupled to the look-up table to generate a carrier NCO value; the carrier NCO comprising:

N carrier base circuits to generate N carrier channel NCO values at a second clock frequency, each of the N carrier base circuits having an increment register to store an increment value loaded from a processor,

a decoder coupled to the N carrier base circuits to enable loading of one of the N increment registers based on a channel select value, and

a multiplexer coupled to the N carrier base circuits to select the carrier NCO value from the N carrier channel NCO values at the first clock frequency.

13. (previously presented) The apparatus of claim 12 wherein $N = 12$.

14. (original) The apparatus of claim 12 wherein the first clock frequency is equal to twenty-four times a coarse/acquisition chip rate of the GPS.

15. (previously presented) The apparatus of claim 12 wherein the second clock frequency is equal to one-quarter times a coarse/acquisition chip rate of the GPS.

16. (canceled) A method comprising:

Appl. No. 09/80,602

Amdt. Dated July 27, 2006

Reply to Final Office action of May 3, 2006

storing K sums of mixer samples during an epoch interval, the mixer samples being generated at a first clock frequency from a mixer for N channels corresponding to N satellites in a global positioning system (GPS) receiver;

generating an address modulo-KN corresponding to a first location in a memory at the first clock frequency; and

adding one of the mixer samples to contents of the first location, the sum being written into the first location.

17. (canceled) The method of claim 16 further comprising:
storing the K sums of mixer samples transferred from the memory at end of the epoch interval.

18. (canceled) The method of claim 16 further comprising:
generating an epoch signal indicative of the epoch interval.

19. (canceled) The method of claim 18 wherein generating an epoch signal comprises:
generating N channel interval signals;
enabling one of the N epoch interval generators; and
selecting one of the N channel interval signals, the selected one of the N channel interval signals corresponding to the epoch signal.

20. (canceled) The method of claim 16 wherein $K = 22$ and $N = 12$.

21. (canceled) The method of claim 20 wherein the first clock frequency is equal to twenty-four times a coarse/acquisition chip rate of the GPS receiver.

22. (canceled) A method comprising:
mixing a dc-spread sample with coefficients to generate a mixer sample at a first clock frequency, the de-spread sample being provided by a de-spreader circuit for a signal received from one of N satellites in a global positioning system (GPS);

Appl. No. 09/80,602
Amdt. Dated July 27, 2006
Reply to Final Office action of May 3, 2006

generating the coefficients based on a carrier numerically controlled oscillator (NCO) value; and
generating a carrier NCO value.

23. (canceled) The method of claim 22 wherein the de-spread sample includes de-spread in-phase and de-spread quadrature components, each component having 6 bits.

24. (canceled) The method of claim 23 wherein the coefficients include a sine and cosine values, each value having three bits.

25. (canceled) The method of claim 24 wherein the mixer sample includes mixer in-phase and quadrature components.

26. (previously presented) A method comprising:
mixing a de-spread sample with coefficients to generate a mixer sample at a first clock frequency, the de-spread sample being provided by a de-spreader circuit for a signal received from one of N satellites in a global positioning system (GPS), the de-spread sample including de-spread in-phase and de-spread quadrature components, each component having 6 bits, the mixer sample includes mixer in-phase and quadrature components, mixing comprising:

generating the mixer in-phase component based on a first complex multiplication on the de-spread in-phase and quadrature components and the sine and cosine values, the mixer in-phase component having 8 bits, and
generating the mixer quadrature component based on a second complex multiplication on the de-spread in-phase and quadrature components and the sine and cosine values, the mixer quadrature component having 8 bits;

generating the coefficients based on a carrier numerically controlled oscillator (NCO) value; and
generating a carrier NCO value.

27. (previously presented) A method comprising:

Appl. No. 09/80,602
Amdt. Dated July 27, 2006
Reply to Final Office action of May 3, 2006

mixing a de-spreaded sample with coefficients to generate a mixer sample at a first clock frequency, the de-spread sample being provided by a de-spreader circuit for a signal received from one of N satellites in a global positioning system (GPS);

generating the coefficients based on a carrier numerically controlled oscillator (NCO) value; and

generating a carrier NCO value, comprising:

generating N carrier channel NCO values at a second clock frequency, each of the N carrier base circuits having an increment register to store an increment value loaded from a processor,

enabling loading of one of the N increment registers based on a channel select value, and

selecting the carrier NCO value from the N carrier channel NCO values at the first clock frequency.

28. (previously presented) The method of claim 27 wherein $N = 12$.

29. (original) The method of claim 27 wherein the first clock frequency is equal to twenty-four times a coarse/acquisition chip rate of the GPS.

30. (previously presented) The method of claim 27 wherein the second clock frequency is equal to one-quarter times a coarse/acquisition chip rate of the GPS.

31. (original) A receiver comprising:

a mixer circuit to mix de-spreaded samples with coefficients to generate mixer samples at a first clock frequency, the de-spread samples being provided by a de-spreader circuit for a signal received from one of N channels corresponding to N satellites in a global positioning system (GPS);

a carrier numerically controlled oscillator (NCO) circuit coupled to the mixer to generate the coefficients based on one of the N channels, the NCO circuit comprising:

a first memory having KN locations to store K sums of the mixer samples during an epoch interval,

Appl. No. 09/80,602
Amdt. Dated July 27, 2006
Reply to Final Office action of May 3, 2006

an address counter coupled to the first memory to generate an address modulo-KN corresponding to a first location in the first memory at the first clock frequency, and
an adder coupled to the mixer and the first memory to add one of the mixer samples to contents of the first location, the sum being written into the first location.

32. (original) The receiver of claim 31 further comprising:
a second memory coupled to the first memory and the address counter to store the K sums of mixer samples transferred from the first memory at end of the epoch interval.
33. (original) The receiver of claim 31 further comprising:
an epoch control circuit to generate an epoch signal indicative of the epoch interval.
34. (original) The receiver of claim 33 wherein the epoch control circuit comprises:
N epoch interval generators to generate N channel interval signals;
a decoder to enable one of the N epoch interval generators; and
a multiplexer coupled to the N epoch interval generators to select one of the N channel interval signals, the selected one of the N channel interval signals corresponding to the epoch signal.
35. (original) The receiver of claim 31 wherein $K = 22$ and $N = 12$.
36. (original) The receiver of claim 35 wherein the first clock frequency is equal to twenty-four times a coarse/acquisition chip rate of the GPS receiver.
37. (canceled) A receiver comprising:
a dc-spread circuit to de-spread a sample for a signal received from one of N satellites in a global positioning system (GPS); and
a Doppler circuit coupled to the de-spread circuit to remove Doppler frequency, the Doppler circuit comprising:

Appl. No. 09/80,602

Amdt. Dated July 27, 2006

Reply to Final Office action of May 3, 2006

a mixer circuit to mix the de-spreaded sample with coefficients to generate a mixer sample at a first clock frequency;
a look-up table coupled to the mixer circuit to generate the coefficients based on a carrier numerically controlled oscillator (NCO) value; and
a carrier NCO coupled to the look-up table to generate a carrier NCO value.

38. (canceled) The receiver of claim 37 wherein the de-spread sample includes de-spread in-phase and de-spread quadrature components, each component having 6 bits.

39. (canceled) The receiver of claim 38 wherein the coefficients include a sine and cosine values, each value having three bits.

40. (canceled) The receiver of claim 39 wherein the mixer sample includes mixer in-phase and quadrature components.

41. (previously presented) A receiver comprising:
a de-spread circuit to de-spread a sample for a signal received from one of N satellites in a global positioning system (GPS); and
a Doppler circuit coupled to the de-spread circuit to remove Doppler frequency, the Doppler circuit comprising:

a mixer circuit to mix the de-spreaded sample with coefficients to generate a mixer sample at a first clock frequency, the de-spread sample including de-spread in-phase and de-spread quadrature components, each component having 6 bits, the mixer sample including mixer in-phase and quadrature components, the mixer circuit comprising:

an in-phase circuit to generate the mixer in-phase component based on a first complex multiplication on the de-spread in-phase and quadrature components and the sine and cosine values, the mixer in-phase component having 8 bits, and
a quadrature circuit to generate the mixer quadrature component based on a second complex multiplication on the de-spread in-phase and quadrature

Appl. No. 09/80,602

Amdt. Dated July 27, 2006

Reply to Final Office action of May 3, 2006

components and the sine and cosine values, the mixer quadrature component having 8 bits;

a look-up table coupled to the mixer circuit to generate the coefficients based on a carrier numerically controlled oscillator (NCO) value, the coefficients including sine and cosine values, each value having three bits; and
a carrier NCO coupled to the look-up table to generate a carrier NCO value.

42. (previously presented) A receiver comprising:

a de-spread circuit to de-spread a sample for a signal received from one of N satellites in a global positioning system (GPS); and

a Doppler circuit coupled to the de-spread circuit to remove Doppler frequency, the Doppler circuit comprising:

a mixer circuit to mix the de-spreaded sample with coefficients to generate a mixer sample at a first clock frequency;

a look-up table coupled to the mixer circuit to generate the coefficients based on a carrier numerically controlled oscillator (NCO) value; and

a carrier NCO coupled to the look-up table to generate a carrier NCO value, the carrier NCO comprising:

N carrier base circuits to generate N carrier channel NCO values at a second clock frequency, each of the N carrier base circuits having an increment register to store an increment value loaded from a processor,

a decoder coupled to the N carrier base circuits to enable loading of one of the N increment registers based on a channel select value, and

a multiplexer coupled to the N carrier base circuits to select the carrier NCO value from the N carrier channel NCO values at the first clock frequency.

43. (previously presented) The receiver of claim 42 wherein $N = 12$.

Appl. No. 09/80,602
Amdt. Dated July 27, 2006
Reply to Final Office action of May 3, 2006

44. (original) The receiver of claim 42 wherein the first clock frequency is equal to twenty-four times a coarse/acquisition chip rate of the GPS.

45. (previously presented) The receiver of claim 42 wherein the second clock frequency is equal to one-quarter times a coarse/acquisition chip rate of the GPS.